

Product Overview

MT9V034: CMOS Image Sensor, Digital, Global Shutter, VGA, 1/3"

For complete documentation, see the data sheet.

ON Semiconductor's focus on pixel performance excellence provides the foundation for this sensor's exceptional image quality with superior color accuracy, low-light sensitivity, and low noise level. This cost-effective CMOS imaging solution enables high speed image capture capabilities, and includes variable functions, including gain, frame rate, and exposure while maintaining low power consumption.

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Type	Megapixels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
MT9V034C12STC-DP		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	Parallel LVDS	RGB	CLCC-48
MT9V034C12STC-DP1		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	LVDS Parallel	RGB	CLCC-48
MT9V034C12STC-DR		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	LVDS Parallel	RGB	CLCC-48
MT9V034C12STM-DP		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	LVDS Parallel	Mono	CLCC-48
MT9V034C12STM-DP1		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	Parallel LVDS	Mono	CLCC-48
MT9V034C12STM-DR		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	LVDS Parallel	Mono	CLCC-48
MT9V034C12STM-DR1		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	Parallel LVDS	Mono	CLCC-48
MT9V034C12STM-TP		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	LVDS Parallel	Mono	CLCC-48
MT9V034C12STM-TR		Pb-free Halide free	Active	CMOS	WVGA	60	1/3 inch	Global Shutter	6.0 x 6.0	Parallel LVDS	Mono	CLCC-48

For more information please contact your local sales support at www.onsemi.com.

Created on: 7/3/2020