

ISL9R460PF2

4 A, 600 V, STEALTH™ Diode

Description

The ISL9R460PF2 is a STEALTH diode optimized for low loss performance in high frequency hard switched applications. The STEALTH family exhibits low reverse recovery current (I_{RR}) and exceptionally soft recovery under typical operating conditions. This device is intended for use as a free wheeling or boost diode in power supplies and other power switching applications. The low I_{RR} and short t_a phase reduce loss in switching transistors. The soft recovery minimizes ringing, expanding the range of conditions under which the diode may be operated without the use of additional snubber circuitry. Consider using the STEALTH diode with an SMPS IGBT to provide the most efficient and highest power density design at lower cost.

Features

- Ultrafast Recovery, $t_{RR} = 17 \text{ ns}$ (@ $I_F = 4 \text{ A}$)
- Max Forward Voltage, $V_F = 2.4 \text{ V}$ (@ $T_C = 25^\circ\text{C}$)
- 600 V Reverse Voltage and High Reliability
- Avalanche Energy Rated
- This Device is Pb-Free and is RoHS Compliant


Applications

- SMPS
- Hard Switched PFC Boost Diode
- UPS Free Wheeling Diode
- Motor Drive FWD
- SMPS FWD
- Snubber Diode




ON Semiconductor®

www.onsemi.com



TO-220, 2-Lead
CASE 221AS

MARKING DIAGRAM



| | |
|---------|---------------------------|
| \$Y | = ON Semiconductor Logo |
| &Z&3 | = Data Code (Year & Week) |
| &K | = Lot |
| R460PF2 | = Specific Device Code |

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ISL9R460PF2

DEVICE MAXIMUM RATINGS $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Rating | Unit |
|----------------|--|------------|--------------------------------------|
| V_{RRM} | Peak Repetitive Reverse Voltage | 600 | V |
| V_{RWM} | Working Peak Reverse Voltage | 600 | V |
| V_R | DC Blocking Voltage | 600 | V |
| $I_{F(AV)}$ | Average Rectified Forward Current ($T_C = 108^\circ\text{C}$) | 4 | A |
| I_{FRM} | Repetitive Peak Surge Current (20 kHz Square Wave) | 8 | A |
| I_{FSM} | Nonrepetitive Peak Surge Current (Halfwave 1 Phase 60 Hz) | 50 | A |
| P_D | Power Dissipation | 22 | W |
| E_{AVL} | Avalanche Energy (0.5 A, 80 mH) | 10 | mJ |
| T_J, T_{STG} | Operating and Storage Temperature Range | -55 to 175 | $^\circ\text{C}$ |
| T_L, T_{PKG} | Maximum Temperature for Soldering Leads at 0.063in (1.6 mm) from Case for 10s Package Body for 10s, See Techbrief TB334 | 300 260 | $^\circ\text{C}$ $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

PACKAGE MARKING AND ORDERING INFORMATION

| Part Number | Top Mark | Package | Packing Method | Reel Size | Tape Width | Quantity |
|-------------|----------|------------|----------------|-----------|------------|----------|
| ISL9R460PF2 | R460PF2 | TO-220F-2L | Tube | N/A | N/A | 50 |

ELECTRICAL CHARACTERISTICS $T_C = 25^\circ\text{C}$ unless otherwise noted

| Parameter | Conditions | Min | Typ | Max | Unit |
|-----------|------------|-----|-----|-----|------|
|-----------|------------|-----|-----|-----|------|

OFF STATE CHARACTERISTICS

| | | | | | | | |
|-------|-------------------------------|----------------------|---------------------------|---|---|-----|---------------|
| I_R | Instantaneous Reverse Current | $V_R = 600\text{ V}$ | $T_C = 25^\circ\text{C}$ | - | - | 100 | μA |
| | | | $T_C = 125^\circ\text{C}$ | - | - | 1.0 | mA |

ON STATE CHARACTERISTICS

| | | | | | | | |
|-------|-------------------------------|--------------------|---------------------------|---|-----|-----|---|
| V_F | Instantaneous Forward Voltage | $I_F = 4\text{ A}$ | $T_C = 25^\circ\text{C}$ | - | 2.0 | 2.4 | V |
| | | | $T_C = 125^\circ\text{C}$ | - | 1.6 | 2.0 | V |

DYNAMIC CHARACTERISTICS

| | | | | | | |
|-------|----------------------|---------------------------------------|---|----|---|----|
| C_J | Junction Capacitance | $V_R = 10\text{ V}, I_F = 0\text{ A}$ | - | 19 | - | pF |
|-------|----------------------|---------------------------------------|---|----|---|----|

SWITCHING CHARACTERISTICS

| | | | | | | |
|----------|-------------------------------|---|---|-----|----|----|
| t_{RR} | Reverse Recovery Time | $I_F = 1\text{ A}, di_F/dt = 100\text{ A}/\mu\text{s}, V_R = 30\text{ V}$ | - | 17 | 20 | ns |
| | | $I_F = 4\text{ A}, di_F/dt = 100\text{ A}/\mu\text{s}, V_R = 30\text{ V}$ | - | 19 | 22 | ns |
| t_{RR} | Reverse Recovery Time | $I_F = 4\text{ A}, di_F/dt = 200\text{ A}/\mu\text{s}, V_R = 390\text{ V}, T_C = 25^\circ\text{C}$ | - | 17 | - | ns |
| I_{RR} | Reverse Recovery Current | | - | 2.6 | - | A |
| Q_{RR} | Reverse Recovered Charge | | - | 22 | - | nC |
| t_{RR} | Reverse Recovery Time | | - | 77 | - | ns |
| S | Softness Factor (t_b/t_a) | $I_F = 4\text{ A}, di_F/dt = 200\text{ A}/\mu\text{s}, V_R = 390\text{ V}, T_C = 125^\circ\text{C}$ | - | 4.2 | - | |
| I_{RR} | Reverse Recovery Current | | - | 2.8 | - | A |
| Q_{RR} | Reverse Recovered Charge | | - | 100 | - | nC |

ISL9R460PF2

ELECTRICAL CHARACTERISTICS $T_C = 25^\circ\text{C}$ unless otherwise noted (continued)

| Parameter | Conditions | Min | Typ | Max | Unit |
|--|-------------------------------|-----|-----|-----|------------------|
| SWITCHING CHARACTERISTICS | | | | | |
| t_{RR} | Reverse Recovery Time | | 54 | | ns |
| S | Softness Factor (t_b/t_a) | | 3.5 | | |
| I_{RR} | Reverse Recovery Current | | 4.3 | | A |
| Q_{RR} | Reverse Recovered Charge | | 110 | | nC |
| di_M/dt | Maximum di/dt during t_b | | 500 | | A/ μs |
| $I_F = 4\text{ A}$, $di_F/dt = 400\text{ A}/\mu\text{s}$, $V_R = 390\text{ V}$, $T_C = 125^\circ\text{C}$ | | | | | |

THERMAL CHARACTERISTICS

| | | | | | |
|-----------------|--|---------|--|-----|---------------------------|
| $R_{\theta JC}$ | Thermal Resistance Junction to Case | | | 5.7 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient | TO-220F | | 70 | $^\circ\text{C}/\text{W}$ |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL PERFORMANCE CURVES

$T_C = 25^\circ\text{C}$ unless otherwise noted




Figure 1. Forward Current vs Forward Voltage




Figure 2. Reverse Current vs Reverse Voltage




Figure 3. t_A and t_B Curves vs Forward Current




Figure 4. t_A and t_B Curves vs di_F/dt

ISL9R460PF2

TYPICAL PERFORMANCE CURVES (continued)

$T_C = 25^\circ\text{C}$ unless otherwise noted




Figure 5. Maximum Reverse Recovery Current vs Forward Current




Figure 6. Maximum Reverse Recovery Current vs di_F/dt




Figure 7. Reverse Recovery Softness vs di_F/dt




Figure 8. Reverse Recovery Charge vs di_F/dt




Figure 9. Junction Capacitance vs Reverse Voltage




Figure 10. DC Current Derating Curve

ISL9R460PF2

TYPICAL PERFORMANCE CURVES (continued)

$T_C = 25^\circ\text{C}$ unless otherwise noted




Figure 11. Normalized Maximum Transient Thermal Impedance

TEST CIRCUIT AND WAVEFORMS




Figure 12. I_{tRR} Test Circuit

$I = 0.5 \text{ A}$
 $L = 80 \text{ mH}$
 $R < 0.1 \Omega$
 $V_{DD} = 200 \text{ V}$
 $E_{AVL} = 1/2LI^2[V_{R(AVL)} / (V_{R(AVL)} - V_{DD})]$
 $Q_1 = \text{IGBT (} B_{VCEs} > \text{DUT } V_{R(AVL)})$




Figure 14. Avalanche Energy Test Circuit




Figure 13. t_{RR} Waveforms and Definitions




Figure 15. Avalanche Current and Voltage Waveforms

MECHANICAL CASE OUTLINE


PACKAGE DIMENSIONS

ON Semiconductor®



TO-220 Fullpack, 2-Lead / TO-220F-2FS
CASE 221AS
ISSUE O

DATE 29 FEB 2012



| | | |
|-------------------------|--|---|
| DOCUMENT NUMBER: | 98AON67438E | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | TO-220 FULLPACK, 2-LEAD / TO-220F-2FS | PAGE 1 OF 1 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:
Voice Mail: 1 800-282-9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative