

FOR ENERGY EFFICIENT INNOVATIONS

THINK ON.

www.onsemi.com

Test Procedure for the NCP1362 HV Evaluation Board




Confidential



Board Electrical Schematic

Ac input voltage



Dc output voltage




Board Picture

Live parts, lethal voltages



Isolated output



Input voltage from 85 V rms to 500 V rms

Output voltage is 12 V
Nominal current is 1.0 A




Needed Equipment

- The needed equipments are the following:
 - ✓ An ac source (85 to 500 V rms, 60 / 50 Hz), needed power is below 30 W
 - ✓ An input ac watt-meter, up to 30 W and 530 V rms
 - ✓ A dc load with Constant Resistance mode absorbing up to 30 V, $V_{in(max)} < 30 \text{ V}$,
 $I_{out(max)} < 2 \text{ A}$
 - ✓ Usually, dc electronic load can display dc V and dc A. If not, an voltmeter and ampmeter will be needed


- *If the load does not use local Kelvin sensors, then the output voltage must be measured at the board level, not at the cable ends.*

Connecting the Board for Testing

Watt-meter
Input power



Electronic load
in CR mode



Test n° 1: No-load Standby

- Apply the input voltage 140 V rms to J1 connector
- Electronic load is disconnected
 - ✓ *Check that output voltage is around 14 V (15 V max)*
 - ✓ *Verify that input power is below 30 mW*
- Apply the input voltage to 425 V rms
 - ✓ *Input power must be below 150 mW*

Test n° 2: Nominal Power

- Apply the input voltage 140 V rms to J1 connector
- Connect electronic load (in CR mode) to J2 connector
- Load is set to 12 Ω
 - ✓ *Check that output voltage is 12.1 V ($\pm 5\%$)*
 - ✓ *Verify that input power is: $14\text{ W} < P_{in} < 16\text{ W}$*
- Apply the input voltage to 425 V rms
- Repeat above steps

Test n°3: Constant Current Regulation – 140 V rms

- Apply the input voltage 140 V rms to J1 connector
- Connect electronic load (in CR mode) to J2 connector
- Load is set to 9.2 Ω
 - ✓ *Check that output voltage is 10 V*
 - ✓ *Check that output current is around 1.1 A*
- Load is set to 7.2 Ω
 - ✓ *Check that output voltage is 8 V*
 - ✓ *Check that output current is around 1.1 A*

Test n° 4: Constant Current Regulation – 425 V rms

- Apply the input voltage 425 V rms to J1 connector
- Connect electronic load (in CR mode) to J2 connector

- Load is set to 8.8 Ω
 - ✓ *Check that output voltage is 10 V*
 - ✓ *Check that output current is around 1.15 A*

- Load is set to 6.9 Ω
 - ✓ *Check that output voltage is 8 V*
 - ✓ *Check that output current is around 1.17 A*

Test n° 5: UVP Protection in CC Regulation

- Apply the input voltage 140 V rms to J1 connector
- Connect electronic load (in CR mode) to J2 connector
- Load is slowly decreased from 12 Ω to 5 Ω
 - ✓ *Check that the controller stops switching when the output voltage drops around 7.5 V*
- Apply the input voltage to 425 V rms
- Repeat above steps