



PIN A1


REFERENCE

## WLCSP4 0.76x0.76x0.605 CASE 567FJ ISSUE C


**DATE 27 MAR 2023** 

## NOTES:


- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- CONTROLLING DIMENSION: MILLIMETERS
- COPLANARITY APPLIES TO THE SPHERICAL CROWNS OF THE SOLDER BALLS.




TOP VIEW



DIM	MILLIME		TERS	
ויונע	MIN. N□M.	MAX.		
Α	0.555	0.605	0,655	
A1	0.180	0.205	0.230	
A2	0.375	0.400	0.425	
b	0.236	0.261	0.286	
D	0.73	0.76	0.79	
Е	0.73	0.76	0.79	
е	0.40 BSC			





## MOUNTING FOOTPRINT\*

For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## **GENERIC MARKING DIAGRAM\***



XXX = Specific Device Code

= Assembly Location Υ = Year W = Work Week = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "■", may or may not be present. Some products may

DESCRIPTION:	WLCSP4 0.76x0.76x0.605		PAGE 1 OF 1
DOCUMENT NUMBER:	98AON79919E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
riot follow trie	Generic Marking.		

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.