



Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

AN-9114

SPM[®] 8 Package Mounting Guidance

Mounting Guidance

This application note shows the electric spacing and mounting guidance of the SPM[®] 8 Package.

Electric Spacing

The electric spacing specification of the SPM 8 Package is shown in Table 1.

Table 1. Typical Electric Spacing of SPM 8 Package

Location	Clearance [mm]	Creepage Distance [mm]
Between Power Terminals	2.90	3.10
Between Control Terminals	1.80	3.40
Between Terminals & H/S	1.25	2.40

Mounting Method and Precautions

When installing a module to a heat sink, excessive uneven fastening force might apply stress to inside chips, which will lead to a damage or degradation of the device. An example of recommended fastening order is shown in Figure 1.




Figure 1. Mounting Screws Fastening Order:
Pre-Screwing: 1 → 2; Final Screwing: 2 → 1

Notes:

- Do not apply excessive torque when mounting screws. Too much torque may cause ceramic cracks as well as destruction of screws and the heat sink.
- Avoid tightening one side at once. Figure 1 shows the recommended torque order for mounting screws. Uneven mounting can cause the SPM ceramic substrate to be damaged. The pre-screwing torque needs to be set as 20~30% of the maximum torque rating.

Table 2. Mounting Torque and Heat Sink Flatness Specifications

Parameter	Conditions	Limits			Unit	
		Min.	Typ.	Max.		
Device Flatness	See Figure 2	-50		+100	μm	
Heat Sink Flatness	See Figure 3	-50		+100	μm	
Mounting Torque	Screw: M3	Recommended 0.9N·m	0.6	0.7	0.8	N·m
		Recommended 9.1kgf·cm	5.9	6.9	7.9	kgf·cm
Weight			5.0		g	

Note:

- SEMS screws (include spring/plain washer, M3) are recommended.




Figure 2. Measurement Points of Package Surface Flatness

Note:

4. The measurement points of flatness of the package surface are package center and four outside corners.




Figure 3. Measurement Point of Heat Sink Flatness

To get the most effective heat dissipation, it is necessary to enlarge the contact area as much as possible to minimize the contact thermal resistance.

Properly apply thermal-conductive grease over the contact surface between the module and the heat sink. It is also useful for preventing the contact surface from corrosion. Furthermore, ensure that the grease should be suitable for stable quality and long endurance within the wide operation temperature range. Use a torque wrench to fasten screws to the specified torque rating. Exceeding the maximum torque limitation might cause a damage or degradation of the package. Also pay attention not to have any foreign object remaining on the contact surface.

Thermal Compound

- Use a minimum. 150 μm layer of thermal grease to the module base plate or to the heat sink
- While fastening the module, a rim of thermal compound must be observed around the mounted module.

Fixing Sequence

- Fix all screws 0.5 N·m under (by hand or driver).
- Apply impact torque 1.5 ~ 2.5 N·m crosswise.
- Use recommended SEMS screw (included spring/plain washer M3).



Figure 4. SEMS Screw (Size M3, Spring Washer 5.0 Φ , Plain Washer 7.5 Φ)

Related Resources

[AN-9112 - Smart Power Module, Motion SPM® 8 Series User's Guide](#)

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local
Sales Representative